TURNERS FALLS MUNICIPAL AIRPORT


ACADEMIC HANGAR


TURNERS FALLS MUNICIPAL AIRPORT TURNERS FALLS, MA 01376

PREPARED FOR
TURNERS FALLS MUNICIPAL AIRPORT
1 AVENUE A
TURNERS FALLS, MA 01376

DD AVAINIC NO	CUEET NO	
DRAWING NO.	SHEET NO.	<u> </u>
G001	1 OF 11	COVER SHEET
	2 OF 11	EXISTING CONDITIONS PLAN
C002	3 OF 11	DEMOLITION PLAN
C101	4 OF 11	SITE PLAN
C102	5 OF 11	GRADING & DRAINAGE PLAN
C103	6 OF 11	EROSION & SEDIMENTATION CONTROL PLAN
C501	7 OF 11	E&S CONTROL NOTES SHEET 1
C502	8 OF 11	E&S CONTROL NOTES SHEET 2
C503	9 OF 11	E&S CONTROL DETAILS
C504	10 OF 11	CIVIL DETAILS
A3.10	11 OF 11	FLOOR PLAN









Gale Associates, In

6 BEDFORD FARMS DRIVE, SUITE 101 BEDFORD, NH 03110

Connecticut I Florida I Maine I Maryland

This drawing and the design and construction features disclosed a proprietary to Gale Associates, Inc. and shall not be altered or reuse whole or part without the express written permission of Gale Associates.

PERMIT SET

NOT FOR CONSTRUCTION

CADEMIC HANGAR
FALLS MUNICIPAL AIRPONNERS FALLS MUNICIPAL AIRPORT

DATE DESCRIPTION

D. DATE DESCRIPTION

ROJECT NO. 719300

ADD FILE 719300_G001

ESIGNED BY CRR/SMB

RAWN BY CRR

HECKED BY SMB

N.T.S.

GRAPHIC SCALE


SHEET TITLE


DRAWING SCALE


- -

COVER SHEET

G001







SITE PLAN NOTES

TURNERS FALLS MUNICIPAL AIRPORT

1 AVENUE A TURNERS FALLS, MA 01376

LOT SHOWN ON ASSESSOR'S SHEET PARCEL IDENTIFICATION 17-0-015, IN THE TOWN OF MONTAGUE, OF FRANKLIN COUNTY, AND THE STATE OF MASSACHUSETTS.

TOPOGRAPHIC AND PROPERTY BOUNDARY INFORMATION WAS OBTAINED BY HUNTLEY ASSOCIATES, P.C. OF PITTSFIELD, MASSACHUSETTS. BURIED UTILITIES WERE LOCATED BY BLOUND HOUND, LLC OF BOSTON, MASSACHUSETTS. MA STATE PLAN COORDINATE AND ELEVATIONS ARE DERIVED BY MA STATE PLAN AND NORTH

THE PURPOSE OF THIS PLAN IS TO SHOW THE EXISTING LAND USE AND SITE LAYOUT FOR A 12,000 SQUARE FOOT EDUCATIONAL HANGAR AND ASSOCIATED SITE IMPROVEMENTS. PARKING FOR FACILTY, STAFF, AND/OR STUDENTS ASSOCIATED WITH THE ACADEMIC HANGAR SHALL BE PROVIDED BY FRANKLIN COUNTY TECHNICAL

SITE SERVICES TO BE MUNICIPAL WATER AND SEWER. UTILITIES TO BE INSTALLED BY THE TURNERS FALLS WATER DEPARTMENT AND THE MONTAGUE CLEAN WATER

SITE IMPROVEMENTS DEPICTED ON THE PLAN SHALL CONFORM TO THE MOST CURRENT EDITION OF THE AMERICAN DISABILITY ACT (ADA) STANDARDS FOR

IT SHALL BE UNLAWFUL TO MODIFY, CHANGE, OR ALTER ANY STRUCTURE SHOWN ON THIS PLAN IN ANY WAY, TO CONVERT OR ALTER ANY STRUCTURE SHOWN ON THIS PLAN, OR CHANGE THE ABOVE USE INDICATED ON THIS PLAN WITHOUT RECEIVING PRIOR APPROVAL FROM THE TOWN OF MONTAGUE PLANNING BOARD.

THE APPLICANT SHALL SUBMIT A COPY OF ALL ENVIRONMENTAL PERMITS OBTAINED TO THE TOWN OF MONTAGUE PLANNING BOARD PRIOR TO CONSTRUCTION AND PROVIDE ANNUAL UP-DATES OF STORMWATER POLLUTION PREVENTION PLAN (S.W.P.P.P) CONTACT INFORMATION.

0. THE OWNER SHALL BE RESPONSIBLE FOR OBTAINING ANY NECESSARY RIGHT-OF-WAYS AND EASEMENTS. HOWEVER, IT SHALL BE THE RESPONSIBILITY OF THE CONTRACTOR TO VERIFY THAT THE OWNER HAS SECURED ANY NECESSARY EASEMENTS. IT IS THE RESPONSIBILITY OF THE CONTRACTOR TO BE FAMILIAR WITH THE APPLICABLE PROVISIONS OF EACH EASEMENT AS THEY APPLY TO THE WORK AND ABIDE BY THOSE PROVISIONS DURING CONSTRUCTION.

IT IS THE RESPONSIBILITY OF THE CONTRACTOR TO REVIEW ALL OF THE DRAWINGS AND SPECIFICATIONS ASSOCIATED WITH THIS PROJECT'S SCOPE OF WORK PRIOR TO THE COMMENCEMENT OF CONSTRUCTION. WRITTEN DIMENSIONS HAVE PRECEDENCE OVER SCALED DIMENSIONS. SHOULD THE CONTRACTOR FIND A CONFLICT WITH THE DOCUMENTS, RELATIVE TO THE SPECIFICATIONS OR APPLICABLE CODES, IT IS THE CONTRACTOR'S RESPONSIBILITY TO NOTIFY THE ENGINEER-OF-RECORD, IN WRITING, PRIOR TO THE INITIATION OF CONSTRUCTION. FAILURE BY THE CONTRACTOR TO NOTIFY THE ENGINEER SHALL CONSTITUTE ACCEPTANCE OF FULL RESPONSIBILITY BY THE CONTRACTOR TO COMPLETE THE SCOPE OF WORK DEFINED BY THE DRAWINGS AND IN FULL CONFORMANCE WITH LOCAL, STATE, AND

12. IT IS THE RESPONSIBILITY OF THE CONTRACTOR TO CONTACT DIG SAFE (888-DIG-SAFE) AT LEASE 72 HOURS PRIOR TO COMMENCING ANY CONSTRUCTION ACTIVITIES.

13. THE CONTRACTOR SHALL COMPLY WITH ALL APPLICABLE REGULATIONS OF THE OCCUPATIONAL SAFETY AND HEALTH ADMINISTRATION (O.S.H.A.).

4. THE CONTRACTOR SHALL BE RESPONSIBLE FOR OBTAINING ANY NECESSARY PERMITS PRIOR TO CONSTRUCTION. IT IS THE RESPONSIBILITY OF THE CONTRACTOR TO BE FAMILIAR WITH THE APPLICABLE PROVISIONS OF EACH PERMIT AS THEY APPLY TO THE WORK AND ABIDE BY THOSE PROVISIONS DURING CONSTRUCTION.

CONTRACTOR SHALL INSTALL AND MAINTAIN AVIATION TRAFFIC CONTROL DEVICES AS NECESSARY AND IN A MANNER CONSISTENT WITH THE MOST CURRENT EDITION OF THE FEDERAL AVIATION ADMINISTRATIOM (FAA) OPERATION SAFETY ON AIRPORTS DURING CONSTRUCTION (AC-150/5370-2G).

CONTRACTOR SHALL INSTALL AND MAINTAIN TRAFFIC CONTROL DEVICES AS NECESSARY AND IN A MANNER CONSISTENT WITH THE MOST CURRENT EDITION OF THE

THE CONTRACTOR IS REQUIRED TO SUBMIT AN AVIATION AND TRAFFIC CONTROL PLAN TO THE AIRPORT MANAGER OF THE TURNERS FALLS MUNICIPAL AIRPORT PRIOR TO PERFORMING ANY ACTIVITIES WITHIN THE AIRPORT PROPERTY. THE TOWN OF MONTAGUE POLICE DEPARTMENT (413-863-8911), TURNERS FALLS FIRE DEPARTMENT (413-863-3210), TOWN OF MONTAGUE PUBLIC WORKS (413-863-2054), AND TURNERS FALLS MUNICIPAL AIRPORT (413-863-0044) ARE TO BE NOTIFIED AT LEAST 24 HOURS

18. THE CONTRACTOR SHALL FURNISH AND MAINTAIN A TELEPHONE NUMBER WHERE THE CONTRACTOR CAN BE REACHED 24 HOURS A DAY, 7 DAYS A WEEK, UNTIL THE

19. ALL DISTURBED AREAS SHALL BE THE RESPONSIBILITY OF THE CONTRACTOR. ALL DISTURBED AREAS SHALL NOT BE LEFT BARE FOR MORE THAN 30 DAYS, SHALL BE STABILIZED IN A MANNER TO MITIGATE EROSION OR SEDIMENTATION FROM EXITING THE LIMIT OF WORK AND SHALL BE RESTORED IN-KIND UPON COMPLETION OF THE PROJECT. THE MAXIMUM AREA ALLOWED TO BE DISTURBED AND LEFT UNSTABILIZED IS TWO (2) ACRES AT ANY ONE TIME. SEE EROSION & SEDIMENTATION CONTROL

20. SUITABLE EXCAVATED MATERIALS MAY BE INCORPORATED INTO THE PROJECT. THIS PROVISION SHALL IN NO WAY RELIEVE THE CONTRACTOR OF THEIR OBLIGATIONS TO REMOVE AND DISPOSE OF ANY MATERIAL DETERMINED BY THE CONTRACTING OFFICER TO BE UNSUITABLE FOR BACKFILLING OR EXCESS SUITABLE MATERIAL.

EXISTING SIGNS IMPACTED BY THIS PROJECT SHALL BE RESET AT NO ADDITIONAL COST TO THE OWNER. PLACEMENT SHALL CONFORM TO THE REQUIREMENTS OF THE MOST CURRENT EDITION OF THE MANUAL ON UNIFORM TRAFFIC CONTROL DEVICES (M.U.T.C.D.).

22. ALL WORK SHALL BE CONSTRUCTED IN ACCORDANCE WITH THE TOWN OF MONTAGUE AND THE STATE OF MASSACHUSETTS DEPARTMENT OF TRANSPORTATION

	SITE PLAN LEGEND	
EXISTING	DESCRIPTION	PROPOSED
	BITUMINOUS PAVEMENT	
	CONCRETE	
	BUILDING	
	GRAVEL	
x x	CHAIN LINK FENCE	
	PROPERTY LINE	
·	PROPERTY BOUND	
	TREE	
· 401.16	LIGHT POST	

GALE

Gale Associates, Inc. Engineers and Planners

BEDFORD FARMS DRIVE, SUITE 101 P 781.335.6465 F 781.335.6467 www.gainc.com

Connecticut I Florida I Maine I Maryland Massachusetts I New Hampshire I Virginia

his drawing and the design and construction features disclosed a oprietary to Gale Associates, Inc. and shall not be altered or reuse hole or part without the express written permission of Gale Associate Inc. Copyright©2023

PERMIT SET

0 ACADEMIC HANGAR S FALLS MUNICIPAL

DATE DESCRIPTION PROJECT NO. 719300 CADD FILE 719300 C101 **DESIGNED BY** CRR/SMB CRR DRAWN BY **CHECKED BY**

IRNER

DRAWING SCALE 1" = 20' **GRAPHIC SCALE** 10' 20'


11/10/23

DATE


SHEET TITLE

SITE PLAN

DRAWING NO.



C102



- ALL SEDIMENT AND EROSION CONTROL MEASURES SHALL BE DONE IN ACCORDANCE WITH THE "MASSACHUSETTS STORMWATER HANDBOOK", PUBLISHED BY THE MASSACHUSETTS DEPARTMENT OF ENVIROMENTAL PROTECTION (MASSDEP); DATED FEBURARY 2008 (OR CURRENT EDITION).
- THOSE AREAS UNDERGOING ACTUAL CONSTRUCTION SHALL BE MAINTAINED IN AN UNTREATED OR UNVEGETATED CONDITION FOR THE MINIMUM TIME REQUIRED. IN GENERAL, ALL DISTURBED AREAS SHALL NOT BE LEFT BARE FOR MORE THAN 30 DAYS, SHALL BE STABILIZED IN A MANNER TO MITIGATE EROSION OR SEDIMENTATION FROM EXITING THE LIMIT OF WORK AND SHALL BE RESTORED IN-KIND UPON COMPLETION OF THE PROJECT. THE MAXIMUM AREA ALLOWED TO BE DISTURBED AND LEFT UNSTABILIZED IS TWO (2) ACRES AT ANY ONE TIME
- IT IS THE RESPONSIBILITY OF THE CONTRACTOR TO INSPECT, MONITOR AND MAINTAIN ALL EROSION CONTROL STRUCTURES; SEE EROSION CONTROL INSPECTION, MONITORING & MAINTENANCE NOTES LOCATED HEREIN.
- SEDIMENT BARRIERS (SILT FENCE, STONE CHECK DAMS, STABILIZED CONSTRUCTION ENTRANCES, ETC.) SHALL BE INSTALLED PRIOR TO ANY SOIL DISTURBANCE OF UP-GRADIENT DRAINAGE AREAS.
- ALL EXISTING STORM DRAINAGE INLETS SHALL BE PROTECTED BY STRAW BALE FILTERS AND CATCH BASIN FILTER BASKETS TO PREVENT ENTRY OF SEDIMENT FROM RUNOFF WATERS INTO THE STORM DRAIN SYSTEM.
- NO TREES ARE TO BE REMOVED FROM AREAS OUTSIDE THE LIMITS OF GRADING OR FROM SPECIFICALLY DESIGNATED UNDISTURBED AREAS WITHIN THE CONSTRUCTION AREA. IF TREES DESIGNATED TO BE SAVED ARE DAMAGED, CONTRACTOR SHALL BE RESPONSIBLE FOR REPLACING THEM AT NO COST TO THE OWNER OR OWNER'S REPRESENTATIVE.
- SLOPES, EITHER PERMANENT OR TEMPORARY, BETWEEN SLOPES THREE HORIZONTAL TO ONE VERTICAL (3:1) TO TWO HORIZONTAL TO ONE VERTICAL (2:1) SHALL BE STABILIZED WITH EROSION CONTROL BLANKETS AND ANCHORED MULCH NETTING (100% BIODEGRADABLE - PLASTIC NETTING WILL NOT BE ALLOWED - AND BE INSTALLED IN ACCORDANCE WITH THE MANUFACTURERS INSTRUCTIONS, SEE DETAIL). SLOPES STEEPER THAN TWO HORIZONTAL TO ONE VERTICAL (2:1) SHALL BE STABILIZED WITH RIPRAP.
- CUT AND FILL AREAS ARE TO BE PERMANENTLY STABILIZED AS SOON AS PRACTICABLE BUT NO LATER THAN 72 HOURS FOLLOWING FINAL GRADING.
- ALL AREAS OF EXPOSED OR DISTURBED SOIL OTHER THAN THE NEWLY STABILIZED STREAM BANK TO BE STABILIZED AS SOON AS PRACTICABLE BUT NO LATER THAN 45 DAYS FROM THE TIME OF INITIAL DISTURBANCE, UNLESS A SHORTER TIME IS SPECIFIED BY LOCAL AUTHORITIES, THE CONSTRUCTION SEQUENCE APPROVED AS PART OF THE ISSUED PERMIT, OR AN INDEPENDENT MONITOR.
- PERMANENT OR TEMPORARY COVER MUST BE IN PLACE BEFORE THE GROWING SEASON ENDS. WHEN SEEDED AREAS ARE MULCHED, PLANTINGS MAY BE MADE FROM EARLY SPRING TO EARLY OCTOBER. WHEN SEEDED AREAS ARE NOT MULCHED, SEED SHOULD BE PLACED FROM EARLY SPRING TO MAY 20 OR FROM AUGUST 15 TO SEPTEMBER 15. NO DISTURBED AREA SHALL BE LEFT EXPOSED DURING WINTER MONTHS (NOVEMBER THROUGH MARCH). SEE WINTER CONSTRUCTION NOTES. PLANT ANNUAL RYE GRASS PRIOR TO OCTOBER 15TH.
- AFTER OCTOBER 15TH: WHERE MULCH IS USED, IT SHALL BE APPLIED AT TWICE THE RATE AS DURING REGULAR CONSTRUCTION SEASON TO PROVIDE ADDITIONAL PROTECTION. SNOW AND ICE SHALL BE REMOVED TO A THICKNESS LESS THAN ONE INCH BEFORE APPLYING MULCH (IF APPLICABLE) TO DISTURBED SOILS. WHERE FINISHED GRADE IS ACHIEVED, OR BEFORE FORECASTED THAW OR SPRING MELT, MULCH MUST BE SECURED WITH EROSION CONTROL NETTING, TRACKING, OR OTHER METHOD. DIVERSION SWALES OR DITCHES WITHOUT STABILIZED VEGETATION BY OCTOBER 15TH SHALL BE STABILIZED WITH STONE FILL OR EROSION CONTROL NETTING AS APPROVED BY OWNER OR OWNER'S DESIGNATED REPRESENTATIVE
- SPECIES CONSIDERED LOCALLY INVASIVE OR NOXIOUS MAY NOT BE USED.
- USE ONLY NON-PHOSPHATE FERTILIZERS WITHIN 20' OF SURFACE WATERS.
- 14. DURING THE CONSTRUCTION PHASE, INTERCEPTED SEDIMENT WILL BE RETURNED TO THE SITE AND RE-GRADED ONTO OPEN AREAS. POST SEEDING SEDIMENT, IF ANY, WILL BE DISPOSED OF IN AN ACCEPTABLE MANNER.
- RE-VEGETATION MEASURES WILL COMMENCE UPON COMPLETION OF CONSTRUCTION EXCEPT AS NOTED ABOVE. ALL DISTURBED AREAS NOT OTHERWISE STABILIZED WILL BE GRADED, SMOOTHED, AND RE-VEGETATED AS FOLLOWS:
- A MINIMUM OF FOUR (4) INCHES OF LOAM WILL BE SPREAD OVER DISTURBED AREAS AND SMOOTHED TO A UNIFORM SURFACE.
- APPLY LIMESTONE AND FERTILIZER ACCORDING TO SOIL TEST. IF SOIL TESTING IS NOT DEEMED FEASIBLE ON SMALL OR VARIABLE SITES. OR WHERE TIMING IS CRITICAL. FERTILIZER MAY BE APPLIED AT THE RATE OF 800 POUNDS PER ACRE OR 18.4 POUNDS PER 1.000 SQUARE FEET USING 10-20-20 (N-P205-K20) OR EQUIVALENT. APPLY GROUND LIMESTONE (EQUIVALENT TO 50% CALCIUM PLUS MAGNESIUM OXIDE) AT A RATE OF 3 TONS PER ACRE (138 LB PER 1,000 SQ. FT.).
- FOLLOWING SEED BED PREPARATION, DITCHES AND BACK SLOPES WILL BE SEEDED WITH A MIXTURE OF 47% CREEPING RED FESCUE, 5% REDTOP, AND 48% TALL FESCUE. THE LAWN AREAS WILL BE SEEDED WITH A PREMIUM TURF MIXTURE OF 44% KENTUCKY BLUEGRASS, 44% CREEPING RED FESCUE, AND 12% PERENNIAL RYE GRASS: SEEDING RATE IS 1.03 LBS PER 1000 SQ. FT. LAWN QUALITY SOD MAY BE SUBSTITUTED FOR SEED.
- 15.4. HAY MULCH AT THE RATE OF 70-90 LBS PER 1000 SQUARE FEET OR A HYDRO- APPLICATION OF CELLULOSE FIBER SHALL BE APPLIED FOLLOWING SEEDING. A SUITABLE BINDER WILL BE USED ON HAY MULCH FOR WIND CONTROL
- 16. ONCE DISTURBED AREAS HAVE BEEN STABILIZED AND VEGETATION IS ESTABLISHED, ALL TEMPORARY EROSION CONTROL MEASURES SHALL BE REMOVED. AREAS DISTURBED BY THE REMOVAL OF THE EROSION CONTROL MEASURES SHALL IMMEDIAETLY STABALIZED IN ACCORDANCE TO THE SPECIFICATIONS OF THESE DRAWINGS.
- AN AREA IS CONSIDERED "STABLE" IF ONE OF THE FOLLOWING HAS OCCURRED: BASE COURSE GRAVELS HAVE BEEN INSTALLED IN AREAS TO BE PAVED: A MINIMUM OF 85% VEGETATED GROWTH HAS BEEN ESTABLISHED; A MINIMUM OF 3" OF NON-EROSIVE MATERIAL (SUCH AS STONE RIP RAP OR A CERTIFIED COMPOST BLANKET) HAS BEEN INSTALLED; OR EROSION CONTROL BLANKETS HAVE BEEN PROPERLY INSTALLED.
- WETLANDS (EXCEPT THOSE WHICH ARE TO BE FILLED IN ACCORDANCE WITH STATE AND FEDERAL REGULATIONS) WILL BE PROTECTED WITH SILT FENCE INSTALLED AT THE EDGE OF THE WETLAND OR THE BOUNDARY OF WETLAND DISTURBANCE.
- 19. IN GENERAL, AREAS WITHIN 100 FEET OF DELINEATED WETLANDS OR STREAMS SHALL HAVE A MAXIMUM PERIOD OF EXPOSURE OF NOT MORE THAN 15 DAYS.
- 20. FOLLOW APPROPRIATE EROSION CONTROL MEASURES PRIOR TO EACH STORM IN ALL AREAS WITHIN 100 FEET OF DELINEATED WETLANDS OR STREAMS.
- 21. THE DETENTION POND SHALL NOT HAVE WATER DIRECTED TO IT UNTIL THE SLOPES HAVE ESTABLISHED A 75% VEGETATIVE GROWTH.
- 22. THE DETENTION POND EMBANKMENT WILL BE MULCHED AT TWICE THE RATE FOR HAY MULCH OR WITH AN EROSION CONTROL BARK MULCH MIX IF THEY ARE NOT FULLY STABILIZED BY NOVEMBER 15TH.

EROSION CONTROL - INSPECTION, MONITORING & MAINTENANCE

- THE CONTRACTOR SHALL PREPARE A STORM WATER POLLUTION PREVENTION PLAN (SWPPP) IN ACCORDANCE WITH THE MASSACHUSETTS DEPARTMENT OF ENVIROMENTAL PROTECTION (MASSDEP) STORMWATER MANAGEMENT STANDARDS. THIS PROJECT IS EXPECTED TO DISTURB 1.0 ACRES; THEREFORE, AN US ENVIRONMENTAL PROTECTION AGENCY (EPA) - GENERAL CONSTRUCTION (GC) NOTICE OF INTENT (NOI) IS REQUIRED TO BE FILED BY THE CONTRACTOR.
- THE CONTRACTOR SHALL MAINTAIN INSPECTION AND REPAIR REPORTS OF EROSION AND SEDIMENT CONTROL MONITORING AND THESE SHALL BE KEPT AT THE PROJECT SITE DURING CONSTRUCTION. THE REPORTS SHALL INCLUDE THE FOLLOWING:
- 2.1. THE INSPECTION DATE;
- NAMES, TITLES, AND QUALIFICATIONS OF PERSONNEL MAKING THE INSPECTION;
- 2.3. WEATHER INFORMATION AND A DESCRIPTION OF ANY DISCHARGES OCCURRING AT THE TIME OF THE INSPECTION;
- LOCATION(S) OF DISCHARGES OF SEDIMENT OR OTHER POLLUTANTS FROM THE SITE;
- LOCATION(S) OF BMPS THAT NEED TO BE MAINTAINED;
- LOCATION(S) OF BMPS THAT FAILED TO OPERATE AS DESIGNED OR PROVED INADEQUATE FOR A PARTICULAR LOCATION;
- LOCATION(S) WHERE ADDITIONAL BMPS ARE NEEDED THAT DID NOT EXIST AT THE TIME OF INSPECTION; AND
- CORRECTIVE ACTION REQUIRED INCLUDING IMPLEMENTATION DATES
- AT LEAST ONCE EVERY 7 CALENDAR DAYS AND DURING OR WITHIN 24 HOURS OF ANY RAIN EVENT IN WHICH 1/2 -INCH OF PRECIPITATION OR MORE FALLS WITHIN A 24-HOUR PERIOD. THE CONTRACTOR SHALL HAVE QUALIFIED PERSONNEL INSPECT ALL CLEARED AND GRADED AREAS OF THE CONSTRUCTION SITE AND ALL TEMPORARY AND PERMANENT EROSION CONTROL MEASURES.
- THIS INSPECTION WILL VERIFY THAT ALL EROSION CONTROL DEVICES ARE IN GOOD AND WORKING CONDITION. DISCHARGE LOCATIONS WILL BE INSPECTED TO VERIFY THAT SEDIMENTS ARE NOT ENTERING THE DRAINAGE SYSTEM AND ARE NOT EXITING THE PROJECT SITE. VEHICLE ACCESS LOCATIONS WILL BE INSPECTED FOR EVIDENCE OF SEDIMENT TRACKING INTO THE PUBLIC RIGHT-OF-WAY.
- ANY OBSERVED ACCUMULATION OF SEDIMENT OFF THE SITE WILL BE IMMEDIATELY REMOVED AND THE AREA RESTORED TO PRE-CONSTRUCTION CONDITIONS.
- TEMPORARY MEASURES: INSPECTION SHALL VERIFY THAT ANY TEMPORARY MEASURES BEING USED BY THE CONTRACTOR ARE CONSTRUCTED AND OPERATING IN ACCORDANCE WITH APPROVED STANDARDS AND SPECIFICATIONS. MEASURES SHALL BE REPAIRED AND ACCUMULATION OF SEDIMENTS SHALL BE CLEANED AS NEEDED

EROSION CONTROL - WINTER CONSTRUCTION

FOR SITE WORK CONSTRUCTION BETWEEN OCTOBER 15TH AND EARLY APRIL THE CONTRACTOR SHALL FOLLOW WINTER CONSTRUCTION EROSION PROTECTION METHODS AS DESCRIBED BELOW

- CHECK ALL PERIMETER EROSION CONTROL MEASURES AND COMPLETE ANY REQUIRED MAINTENANCE AND REPAIR BEFORE THE GROUND FREEZES.
- PUT IN PLACE ANY ADDITIONALLY NECESSARY EROSION CONTROL MEASURES; DIVERSION DIKES, HAY BALES, SILT FENCE, SEDIMENT TRAPS AND/OR BASINS, ETC. TO PROTECT DOWNSTREAM WATER QUALITY FROM ANTICIPATED WINTER WORK PRIOR TO GROUND FREEZING.
- ALL PROPOSED VEGETATED AREAS WHICH DO NOT EXHIBIT A MINIMUM OF 85% VEGETATIVE GROWTH BY OCTOBER 15TH, OR WHICH ARE DISTURBED AFTER OCTOBER 15TH, SHALL BE STABILIZED BY SEEDING AND INSTALLING EROSION CONTROL BLANKETS ON SLOPES GREATER THAN 3:1, AND SEEDING AND PLACING 3 TO 4 TONS OF MULCH PER ACRE, SECURED WITH ANCHORED NETTING. ELSEWHERE. THE INSTALLATION OF EROSION CONTROL BLANKETS OR MULCH AND NETTING SHALL NOT OCCUR OVER ACCUMULATED SNOW OR ON FROZEN GROUND AND SHALL BE COMPLETED IN ADVANCE OF THAW OR SPRING MELT EVENTS.
- ALL DITCHES OR SWALES THAT DO NOT EXHIBIT A MINIMUM OF 85% VEGETATIVE GROWTH BY OCTOBER 15TH OR THAT ARE DISTURBED AFTER OCTOBER 15TH SHALL BE STABILIZED WITH STONE OR EROSION CONTROL BLANKETS APPROPRIATE FOR THE DESIGN FLOW CONDITIONS.
- AFTER NOVEMBER 15TH, INCOMPLETE ROAD OR PARKING SURFACES, WHERE WORK HAS STOPPED FOR THE WINTER SEASON, SHALL BE PROTECTED WITH A MINIMUM OF 3-INCHES OF CRUSHED GRAVEL PER MASSDOT ITEM M1.03.1, OR IF CONSTRUCTION IS TO CONTINUE THROUGH THE WINTER SEASON, BE CLEARED OF ANY ACCUMULATED SNOW AFTER EACH STORM EVENT
- INSPECT THE EROSION AND SEDIMENT CONTROL MEASURES MORE FREQUENTLY THAN IS SPECIFIED IN THE EROSION CONTROL INSPECTION, MONITORING, AND MAINTENANCE SPECIFICATIONS FOUND ON THIS SHEET DURING THE WINTER AND SPRING THAW MONTHS TO PREVENT FAILURE AND/OR OVERLOADING
- BEFORE PREDICTED THAWS AND/OR HEAVY RAIN EVENTS CHECK ALL MEASURES TO ENSURE THAT THEY WILL BE ABLE TO HANDLE POTENTIALLY HEAVY AND INTENSE RUNOFF AND SEDIMENTATION.
- CONTRACTOR SHALL BE PREPARED TO INSTALL A SECOND LINE OF DEFENSE IF PROBLEMS WITH IN-PLACE EROSION CONTROL MEASURES OCCUR DURING WINTER THAW AND SPRING RAIN EVENTS.
- AS EARLY AS PRACTICAL OF THE NEXT GROWING SEASON, CONTRACTOR SHALL STABILIZE COMPLETED AREAS WITH PERMANENT VEGETATIVE CONTROLS AS SPECIFIED ON THESE DRAWINGS

EROSION CONTROL - SOIL STOCKPILE PRACTICES

- STOCKPILES SHALL BE LOCATE A MINIMUM OF 50 FEET AWAY FROM CONCENTRATED FLOWS OF STORMWATER, DRAINAGE COURSES, AND INLETS.
- STOCKPILES SHALL BE PROTECTED FROM STORMWATER RUN-ON USING TEMPORARY PERIMETER MEASURES SUCH AS DIVERSIONS, BERMS, SANDBAGS, OR OTHER APPROVED PRACTICE.
- STOCKPILES SHALL BE SURROUNDED BY SEDIMENT BARRIERS TO PREVENT MIGRATION OF MATERIAL BEYOND THE IMMEDIATE CONFINES OF THE STOCKPILES.
- STOCKPILES SHALL BE PROTECTED FROM WIND EROSION CONTROL PRACTICES AS APPROPRIATE.
- PROTECTION OF INACTIVE STOCKPILES:
 - 5.1. COVER WITH ANCHORED TARPS OR PROTECT WITH SOIL STABILIZATION MEASURES (TEMPORARY SEED AND MULCH OR OTHER TEMPORARY STABILIZATION PRACTICE) AND
 - TEMPORARY PERIMETER SEDIMENT BARRIERS AT ALL TIMES. CONCRETE RUBBLE, ASPHALT CONCRETE RUBBLE, AGGREGATE MATERIALS, AND OTHER SIMILAR MATERIALS TO BE PROTECTED WITH TEMPORARY SEDIMENT PERIMETER BARRIERS AT ALL TIMES. IF THE MATERIALS ARE A SOURCE OF DUST, THEY ARE TO BE COVERED.
- PROTECTION OF ACTIVE STOCKPILES:
 - SURROUND WITH TEMPORARY LINEAR SEDIMENT BARRIERS PRIOR TO THE ONSET OF PRECIPITATION. PERIMETER BARRIERS TO BE MAINTAINED AT ALL TIMES, AND ADJUSTED AS NEEDED TO ACCOMMODATE THE DELIVERY AND REMOVAL OF MATERIALS FROM THE STOCKPILE. THE INTEGRITY OF THE BARRIER TO BE INSPECTED AT THE END OF EACH WORKING
 - WHEN A STORM EVENT IS PREDICTED, STOCKPILES TO BE PROTECTED WITH AN ANCHORED PROTECTIVE COVERING.
- MAINTENANCE REQUIREMENTS:
 - 7.1. INSPECT ALL SOIL STOCKPILES IMMEDIATELY AFTER STORM EVENTS AND AT THE FREQUENCIES SPECIFIED IN THE PROJECT EROSION AND SEDIMENT CONTROL PLAN AND IN APPLICABLE PERMITS. AT A MINIMUM. INSPECT WEEKLY DURING WET WEATHER PERIODS TO VERIFY THAT EROSION AND SEDIMENT CONTROL MEASURES ARE IN PLACE AND FUNCTIONING PROPERLY.
 - REPAIR AND/OR REPLACE PERIMETER CONTROLS AND STOCKPILE COVERINGS AS NEEDED TO KEEP THEM FUNCTIONING PROPERLY.



Gale Associates, Inc. Ingineers and Planners

BEDFORD FARMS DRIVE, SUITE 101 BEDFORD, NH 03110 781.335.6465 F 781.335.6467 www.gainc.com

Connecticut I Florida I Maine I Maryland lassachusetts I New Hampshire I Virginia

his drawing and the design and construction features disclosed a oprietary to Gale Associates, Inc. and shall not be altered or reused ole or part without the express written permission of Gale Associate Inc. Copyright©2023

PERMIT SET

AIRPOR

CADEMIC HANGAR FALLS MUNICIPAL

DATE DESCRIPTION

Ŕς

PROJECT NO. 719300 CADD FILE 719300 C501 **DESIGNED BY** CRR/SMB DRAWN BY CHECKED BY DATE 11/10/23 DRAWING SCALE NTS

GRAPHIC SCALE

SHEET TITLE

EROSION & SEDIMENTATION CONTROL NOTES

DRAWING NO.

1. SITE PREPARATION:

- 1.1. INSTALL NEEDED EROSION AND SEDIMENT CONTROL MEASURES SUCH AS SILTATION BARRIERS, DIVERSIONS, AND SEDIMENT TRAPS
- 1.2. GRADE AS NEEDED FOR THE ACCESS OF EQUIPMENT FOR SEEDBED PREPARATION, SEEDING, MULCH APPLICATION, AND MULCH ANCHORING.
- 1.3. RUNOFF SHOULD BE DIVERTED FROM THE SEEDED AREA.
- 1.4. ON SLOPES 4:1 OR STEEPER, THE FINAL PREPARATION SHOULD INCLUDE CREATING HORIZONTAL GROOVES PERPENDICULAR TO THE DIRECTION OF THE SLOPE TO CATCH SEED AND REDUCE RUNOFF.

2. SEEDBED PREPARATION:

- 2.1. STONES AND TRASH SHALL BE REMOVED SO AS NOT TO INTERFERE WITH THE SEEDING AREA.
- 2.2. WHERE THE SOIL HAS BEEN COMPACTED BY CONSTRUCTION OPERATIONS, LOOSEN SOIL TO A DEPTH OF 2 INCHES BEFORE APPLYING FERTILIZER, LIME AND SEED.
- 2.3. IF APPLICABLE, FERTILIZER AND ORGANIC SOIL AMENDMENTS SHOULD BE APPLIED DURING THE GROWING SEASON.
 - 2.3.1. APPLY LIMESTONE AND FERTILIZER ACCORDING TO SOIL TEST RECOMMENDATIONS. IF SOIL TESTING IS NOT FEASIBLE ON SMALL OR VARIABLE SITES, OR WHERE TIMING IS CRITICAL, FERTILIZER MAY BE APPLIED AT THE RATE OF 600 POUNDS PER ACRE OR 13.8 POUNDS PER 1,000 SQUARE FEET OF LOW PHOSPHATE FERTILIZER1 (N-P2O5-K2O) OR EQUIVALENT. APPLY LIMESTONE (EQUIVALENT TO 50 PERCENT CALCIUM PLUS MAGNESIUM OXIDE) AT A RATE OF 3 TONS PER ACRE (138 LB. PER 1,000 SQUARE FEET).
 - 2.3.2. FERTILIZER SHOULD BE RESTRICTED TO A LOW PHOSPHATE (LESS THAN 2% PHOSPHORUS), SLOW RELEASE NITROGEN (AT LEAST 50% SLOW RELEASE COMPONENT)
 FERTILIZER WHEN APPLIED TO AREAS BETWEEN 25 FEET AND 250 FEET FROM A SURFACE WATER BODY. NO FERTILIZER EXCEPT LIMESTONE SHOULD BE APPLIED WITHIN 25
 FEET OF A SURFACE WATER BODY. THESE LIMITATIONS ARE REQUIREMENTS FOR ANY WATER BODY PROTECTED BY THE COMPREHENSIVE SHORELAND PROTECTION ACT.

13. SEEDIN

- 3.1. APPLY SEED UNIFORMLY BY HAND, CYCLONE SEEDER, DRILL, CULTIPACKER TYPE SEEDER OR HYDROSEEDER (SLURRY INCLUDING SEED AND FERTILIZER). NORMAL SEEDING DEPTH IS FROM 1/4 TO 1/2-INCH. HYDROSEEDING THAT INCLUDES MULCH MAY BE LEFT ON SOIL SURFACE. SEEDING RATES MUST BE INCREASED 10% WHEN HYDROSEEDING.
- 3.2. TEMPORARY SEEDING SHOULD TYPICALLY OCCUR PRIOR TO SEPTEMBER 15TH.
- 3.3. AREAS SEEDED BETWEEN MAY 15TH AND AUGUST 15TH SHOULD BE COVERED WITH HAY OR STRAW MULCH, ACCORDING TO THE "TEMPORARY AND PERMANENT MULCHING" PRACTICE.
- 3.4. VEGETATED GROWTH COVERING AT LEAST 85% OF THE DISTURBED AREA SHOULD BE ACHIEVED PRIOR TO OCTOBER 15TH. IF THIS CONDITION IS NOT ACHIEVED, IMPLEMENT OTHER TEMPORARY STABILIZATION MEASURES FOR WINTER PROTECTION.

3.5. RECOMMENDED SEEDING:

SPECIES	LBS/Ac	LBS/1k	REMARKS
WINTER RYE	112	2.5	FALL SEEDING (8/15-9/15). SEED TO A 1" DEPTH.
OAK	80	2.0	SPRING SEEDING (4/15-5/15). SEED TO A 1" DEPTH.
ANNUAL RYEGRASS	40	1.7	EARLY SPRING/FALL SEEDING. 1/4" COVER OVER SEED.
PERENNAL RYEGRASS	30	0.7	SUMMER/FALL SEEDING. SEED TO 1/2" DEPTH.

4. MAINTENANCE REQUIREMENTS

- 4.1. TEMPORARY SEEDING SHOULD BE INSPECTED WEEKLY AND AFTER ANY RAINFALL EXCEEDING ½ INCH IN 24 HOURS ON ACTIVE CONSTRUCTION SITES.
- 4.2. TEMPORARY SEEDING SHOULD BE INSPECTED JUST PRIOR TO SEPTEMBER 15, TO ASCERTAIN WHETHER ADDITIONAL SEEDING IS REQUIRED TO PROVIDE STABILIZATION OVER THE WINTER PERIOD.
- 4.3. BASED ON INSPECTION, AREAS SHOULD BE RESEEDED TO ACHIEVE FULL STABILIZATION OF EXPOSED SOILS. IF IT IS TOO LATE IN THE PLANTING SEASON TO APPLY ADDITIONAL SEED, THEN OTHER TEMPORARY STABILIZATION MEASURES SHOULD BE IMPLEMENTED.
- 4.4. AT A MINIMUM, 85% OF THE SOIL SURFACE SHOULD BE COVERED BY VEGETATION.
- 4.5. IF ANY EVIDENCE OF EROSION OR SEDIMENTATION IS APPARENT, REPAIRS SHOULD BE MADE AND AREAS SHOULD BE RESEEDED, WITH OTHER TEMPORARY MEASURES (E.G., MULCH) USED TO PROVIDE EROSION PROTECTION DURING THE PERIOD OF VEGETATION ESTABLISHMENT.

3.12.11.2.7.1.31.1.31.1.

- 1.1. INSTALL NEEDED EROSION AND SEDIMENT CONTROL MEASURES SUCH AS SILTATION BARRIERS, DIVERSIONS, AND SEDIMENT TRAPS.
- 1.2. GRADE AS NEEDED FOR THE ACCESS OF EQUIPMENT FOR SEEDBED PREPARATION, SEEDING, MULCH APPLICATION, AND MULCH ANCHORING
- 1.3. RUNOFF SHOULD BE DIVERTED FROM THE SEEDED AREA.
- 1.4. ON SLOPES 4:1 OR STEEPER, THE FINAL PREPARATION SHOULD INCLUDE CREATING HORIZONTAL GROOVES PERPENDICULAR TO THE DIRECTION OF THE SLOPE TO CATCH SEED AND REDUCE RUNOFF.

2. SEEDBED PREPARATION:

- 2.1. WORK LIME AND FERTILIZER INTO THE SOIL AS NEARLY AS PRACTICAL TO A DEPTH OF 4 INCHES WITH A DISC, SPRING TOOTH HARROW OR OTHER SUITABLE EQUIPMENT. THE FINAL HARROWING OPERATION SHOULD BE ON THE GENERAL CONTOUR. CONTINUE TILLAGE UNTIL A REASONABLY UNIFORM, FINE SEEDBED IS PREPARED. ALL BUT CLAY OR SILTY SOILS AND COARSE SANDS SHOULD BE ROLLED TO FIRM THE SEEDBED WHEREVER FEASIBLE.
- 2.2. REMOVE FROM THE SURFACE ALL STONES 2 INCHES OR LARGER IN ANY DIMENSION. REMOVE ALL OTHER DEBRIS, SUCH AS WIRE, CABLE, TREE ROOTS, CONCRETE, CLODS, LUMPS, TRASH OR OTHER UNSUITABLE MATERIAL.
- 2.3. INSPECT SEEDBED JUST BEFORE SEEDING. IF TRAFFIC HAS LEFT THE SOIL COMPACTED; THE AREA MUST BE TILLED AND FIRMED AS ABOVE.
- 2.4. WHERE THE SOIL HAS BEEN COMPACTED BY CONSTRUCTION OPERATIONS, LOOSEN SOIL TO A DEPTH OF 2 INCHES BEFORE APPLYING FERTILIZER, LIME AND SEED.
- 2.5. IF APPLICABLE, FERTILIZER AND ORGANIC SOIL AMENDMENTS SHOULD BE APPLIED DURING THE GROWING SEASON
 - 2.5.1. APPLY LIMESTONE AND FERTILIZER ACCORDING TO SOIL TEST RECOMMENDATIONS. IF SOIL TESTING IS NOT FEASIBLE ON SMALL OR VARIABLE SITES, OR WHERE TIMING IS CRITICAL, FERTILIZER MAY BE APPLIED AT THE RATE OF 600 POUNDS PER ACRE OR 13.8 POUNDS PER 1,000 SQUARE FEET OF LOW PHOSPHATE FERTILIZER1 (N-P2O5-K2O) OR EQUIVALENT. APPLY LIMESTONE (EQUIVALENT TO 50 PERCENT CALCIUM PLUS MAGNESIUM OXIDE) AT A RATE OF 3 TONS PER ACRE (138 LB. PER 1,000 SQUARE FEET).
 - 2.5.2. FERTILIZER SHOULD BE RESTRICTED TO A LOW PHOSPHATE (LESS THAN 2% PHOSPHORUS), SLOW RELEASE NITROGEN (AT LEAST 50% SLOW RELEASE COMPONENT)
 FERTILIZER WHEN APPLIED TO AREAS BETWEEN 25 FEET AND 250 FEET FROM A SURFACE WATER BODY. NO FERTILIZER EXCEPT LIMESTONE SHOULD BE APPLIED WITHIN 25
 FEET OF A SURFACE WATER BODY. THESE LIMITATIONS ARE REQUIREMENTS FOR ANY WATER BODY PROTECTED BY THE COMPREHENSIVE SHORELAND PROTECTION ACT.

3. SEEDING:

- 3.1. INOCULATE ALL LEGUME SEED WITH THE CORRECT TYPE AND AMOUNT OF INOCULANT.
- 3.2. APPLY SEED UNIFORMLY BY HAND, CYCLONE SEEDER, DRILL, CULTIPACKER TYPE SEEDER OR HYDROSEEDER (SLURRY INCLUDING SEED AND FERTILIZER). NORMAL SEEDING DEPTH IS FROM ¼ TO ½ INCH. HYDROSEEDING THAT INCLUDES MULCH MAY BE LEFT ON SOIL SURFACE. SEEDING OPERATIONS SHOULD BE ON THE CONTOUR.
- 3.3. WHERE FEASIBLE, EXCEPT WHERE EITHER A CULTIPACKER TYPE SEEDER OR HYDROSEEDER IS USED, THE SEEDBED SHOULD BE FIRMED FOLLOWING SEEDING OPERATIONS WITH A ROLLER, OR LIGHT DRAG.
- 3.4. SPRING SEEDING USUALLY GIVES THE BEST RESULTS FOR ALL SEED MIXES OR WITH LEGUMES. PERMANENT SEEDING SHOULD BE COMPLETED 45 DAYS PRIOR TO THE FIRST KILLING FROST. WHEN CROWN VETCH IS SEEDED IN LATER SUMMER, AT LEAST 35% OF THE SEED SHOULD BE HARD SEED (UNSCARIFIED). IF SEEDING CANNOT BE DONE WITHIN THE SPECIFIED SEEDING DATES, MULCH ACCORDING TO THE "TEMPORARY AND PERMANENT MULCHING PRACTICE," AND DELAY SEEDING UNTIL THE NEXT RECOMMENDED SEEDING PERIOD.
 - 3.4.1. TEMPORARY SEEDING SHOULD TYPICALLY OCCUR PRIOR TO SEPTEMBER 15TH.
 - 3.4.2. AREAS SEEDED BETWEEN MAY 15TH AND AUGUST 15TH SHOULD BE COVERED WITH HAY OR STRAW MULCH, ACCORDING TO THE "TEMPORARY AND PERMANENT MULCHING" PRACTICE PRESENTED IN THE "NEW HAMPSHIRE STORMWATER MANAGEMENT MANUAL VOLUME 3 CONSTRUCTION PHASE EROSION AND SEDIMENT CONTROLS".
- 3.5. VEGETATED GROWTH COVERING AT LEAST 85% OF THE DISTURBED AREA SHOULD BE ACHIEVED PRIOR TO OCTOBER 15TH. IF THIS CONDITION IS NOT ACHIEVED, IMPLEMENT TEMPORARY STABILIZATION MEASURES FOR OVERWINTER PROTECTION, AND COMPLETE PERMANENT SEED STABILIZATION DURING THE NEXT GROWING SEASON.

4 HYDROSEEDING

- 4.1. WHEN HYDROSEEDING (HYDRAULIC APPLICATION), PREPARE THE SEEDBED AS SPECIFIED ABOVE OR BY HAND RAKING TO LOOSEN AND SMOOTH THE SOIL AND TO REMOVE SURFACE STONES LARGER THAN 2 INCHES IN DIAMETER.
- 4.2. SLOPES MUST BE NO STEEPER THAN 2 TO 1 (2 FEET HORIZONTALLY TO 1 FOOT VERTICALLY).
- 1.3. LIME AND FERTILIZER MAY BE APPLIED SIMULTANEOUSLY WITH THE SEED. THE USE OF FIBER MULCH ON CRITICAL AREAS IS NOT RECOMMENDED (UNLESS IT IS USED TO HOLD STRAW OR HAY). BETTER PROTECTION IS GAINED BY USING STRAW MULCH AND HOLDING IT WITH ADHESIVE MATERIALS OR 500 POUNDS PER ACRE OF WOOD FIBER MULCH.
- 4.4. SEEDING RATES MUST BE INCREASED 10% WHEN HYDROSEEDING.
- 4.5. RECOMMENDED SEEDING:

SPECIES	LBS/Ac	LBS/1k
TALL FESCUE	20	0.45
CREEPING RED FESCUE	20	0.45
REDTOP	2	0.05
TOTAL	42	0.95

MAINTENANCE REQUIREMENTS

- 5.1. PERMANENT SEEDED AREAS SHOULD BE INSPECTED AT LEAST MONTHLY DURING THE COURSE OF CONSTRUCTION. INSPECTIONS, MAINTENANCE, AND CORRECTIVE ACTIONS SHOULD CONTINUE UNTIL THE OWNER ASSUMES PERMANENT OPERATION OF THE SITE.
- 5.2. SEEDED AREAS SHOULD BE MOWED AS REQUIRED TO MAINTAIN A HEALTHY STAND OF VEGETATION, WITH MOWING HEIGHT AND FREQUENCY DEPENDENT ON TYPE OF GRASS COVER.
- 5.3. BASED ON INSPECTION, AREAS SHOULD BE RESEEDED TO ACHIEVE FULL STABILIZATION OF EXPOSED SOILS.
- 5.4. AT A MINIMUM, 85% OF THE SOIL SURFACE SHOULD BE COVERED BY VEGETATION.
- .5. IF ANY EVIDENCE OF EROSION OR SEDIMENTATION IS APPARENT, REPAIRS SHOULD BE MADE AND AREAS SHOULD BE RESEEDED, WITH OTHER TEMPORARY MEASURES (E.G., MULCH)
 USED TO PROVIDE EROSION PROTECTION DURING THE PERIOD OF VEGETATION ESTABLISHMENT.

GALE

Gale Associates, Inc.
Engineers and Planners

6 BEDFORD FARMS DRIVE, SUITE 101 BEDFORD, NH 03110 P 781.335.6465 F 781.335.6467 www.gainc.com

Connecticut I Florida I Maine I Maryland Massachusetts I New Hampshire I Virginia

This drawing and the design and construction features disclosed are proprietary to Gale Associates, Inc. and shall not be altered or reused in whole or part without the express written permission of Gale Associates

Inc. Copyright©2023





IRPORT

OWNER
ERS FALLS MUNICIPAL AIRPORT
1 AVENUE A

CADEMIC HANGAI FALLS MUNICIPAL

ഗ≻

PATE DESCRIPTION

NO. DATE DESCRIPTION BY

PROJECT NO. 719300

CADD FILE 719300_C501

DESIGNED BY CRR/SMB

DRAWN BY CRR

CHECKED BY SMB

DATE 11/10/23

DRAWING SCALE NTS


GRAPHIC SCALE

SHEET TITLE


EROSION &
SEDIMENTATION
CONTROL
NOTES

C502


DRAWING NO.



f:\719300\plots\d - site plan - final\719300 C501.dwg. 11/8/2023 11:22:45 AM. AutoCAD PDF (General Documentation).r



f:\719300\plots\d - site plan - final\719300_C501.dwg, 11/8/2023 11:22:46 AM, AutoCAD PDF (General Documentation).pc3





167 Main St Brattleboro VT 05301

Turners
Falls Airport
Aviation Hanger

Turners Falls, MA 01376

SD 14/June/2023



A3.10
2023 © Austin Design Cooperative, Inc.